

Safety data sheet

Page: 1/7

BASF Construction Chemicals Safety data sheet according to 91/155/EEC

Date / Revised: 2007/12/15

Product: **UCRETE HP HPQ NEUTRAL PTC**

Version: 1.0

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009

1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION

UCRETE HP HPQ NEUTRAL PTC

Company:

BASF Construction Chemicals
100 Campus Drive
Florham Park, NJ 07932

Emergency information:

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. HAZARDOUS INGREDIENTS

| <u>Chemical</u> | <u>CAS No.</u> | <u>TLV</u> | <u>STEL</u> | <u>PEL</u> | <u>CEIL</u> | <u>Weight %</u> |
|----------------------------|----------------|------------------------|-------------|-----------------------|-------------|------------------|
| SILICA, CRYSTALLINE QUARTZ | 14808-60-7 | 0.05 mg/m ³ | N.E. | 0.1 mg/m ³ | N.E. | 60.00 - 100.00 % |
| PORTLAND CEMENT | 65997-15-1 | 10 mg/m ³ | N.E. | 5 mg/m ³ | N.E. | 10.00 - 30.00 % |
| IRON OXIDE | 1309-37-1 | 5 mg/m ³ | N.E. | 10 mg/m ³ | N.E. | 1.00 - 5.00 % |

3. HAZARDS IDENTIFICATION

| HMIS® Rating | HEALTH | FLAMMABILITY | PHYSICAL HAZARD |
|-------------------------|---------------------------------------------|--------------|-----------------|
| | 2* | 0 | 1 |
| WHMIS Class | : D2B E | | |
| Primary Routes of Entry | : Inhalation Eye contact Skin contact | | |

BASF Construction Chemicals Safety data sheet according to 91/155/EEC
 Date / Revised: 2007/12/15
 Product: **UCRETE HP HPQ NEUTRAL PTC**

Version: 1.0

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009

Effects of Overexposure

- Inhalation : Inhalation of dust can cause coughing and labored breathing and possible temporary but reversible irritation on mucous membranes and respiratory tract.
- Skin : Can cause slight to moderate irritation due to abrasive action. In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.
- Eyes : Can cause severe irritation, redness, tearing and blurred vision. Prolonged or repeated contact can cause burns and possibly corneal injury.
- Ingestion : Irritating to mouth, throat and stomach.
- Chronic exposure : This product contains Crystalline (quartz) Silica which has been listed as a human carcinogen by NTP (Group 1) and IARC (Human Carcinogen) and a Suspected Human Carcinogen by ACGIH (category A2). Repeated or prolonged over exposure to free respirable Crystalline (quartz) silica can cause silicosis or other delayed and serious lung injury. Repeated or prolonged overexposure to free respirable silica can cause silicosis or other delayed and serious lung injury.

Carcinogenicity

| | ACGIH | IARC | NTP | OSHA |
|----------------------------|-----------------------------------------|------------------------------------------------|------|------|
| SILICA, CRYSTALLINE QUARTZ | Suspected human carcinogen. | Human carcinogen. | | N.E. |
| PORTLAND CEMENT | N.E. | N.E. | N.E. | N.E. |
| IRON OXIDE | Not classifiable as a human carcinogen. | Classification not possible from current data. | N.E. | N.E. |

4. FIRST AID MEASURES

- Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. Call a physician immediately. Never give anything by mouth to an unconscious person. If a person vomits, place him/her in the recovery position.
- Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : Not combustible.
- Autoignition temperature : Not combustible.
- Lower explosion limit : not applicable
- Upper explosion limit : not applicable

BASF Construction Chemicals Safety data sheet according to 91/155/EEC

Date / Revised: 2007/12/15

Version: 1.0

Product: **UCRETE HP HPQ NEUTRAL PTC**

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009

- Suitable extinguishing media : water fog
carbon dioxide (CO₂)
dry chemical
alcohol-resistant foam
- Fire and Explosion Hazards : This product is alkaline and releases considerable heat on contact with small amounts of water. Avoid contact between resulting hot alkaline paste and metallic aluminum. Such contact could generate hydrogen gas.
- Special Fire-fighting Procedures : As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Clean thoroughly. After cleaning, flush away traces with water. Keep in suitable, closed containers for disposal. Wear personal protective equipment (refer to section 8).

7. HANDLING AND STORAGE

- Handling : Use only in area provided with appropriate ventilation. Keep out of reach of children. Avoid exceeding of the given occupational exposure limits (see section 2). Avoid formation of respirable particles.
- Storage : Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Eye protection : Wear as appropriate:
safety glasses with side-shields
face-shield
goggles
- Hand protection : Wear as appropriate:
impervious gloves
- Body Protection : Wear as appropriate:
preventive skin protection
impervious clothing
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
- Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.
- Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

BASF Construction Chemicals Safety data sheet according to 91/155/EEC

Date / Revised: 2007/12/15

Version: 1.0

Product: **UCRETE HP HPQ NEUTRAL PTC**

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009

| | | |
|---------------------------------------------------------------|---|-------------------|
| Color | : | grey |
| Physical State | : | powder |
| Odor | : | none |
| pH (at 100 %) | : | not applicable |
| Odor Threshold | : | no data available |
| Vapor Pressure | : | not applicable |
| Vapor Density | : | not applicable |
| Boiling point/range | : | no data available |
| Freeze Point | : | no data available |
| Water solubility | : | slightly soluble |
| Specific Gravity | : | no data available |
| Viscosity | : | no data available |
| Evaporation rate | : | no data available |
| Partition coefficient (n-octanol/water) | : | no data available |
| VOC Concentration as applied (less water and exempt solvents) | : | 0 g/l |

10. STABILITY AND REACTIVITY

| | | |
|----------------------------------|---|----------------------------------------------------------|
| Stability | : | Stable under recommended storage conditions. |
| Conditions to avoid | : | no data available |
| Materials to avoid | : | strong acids and strong bases strong oxidizing agents |
| Hazardous decomposition products | : | no data available |
| Hazardous polymerization | : | Will not occur under normal conditions. |

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

| <u>Product</u> | <u>Type</u> LC50 | <u>Value</u> no data available | <u>Species</u> | <u>Exposure time</u> |
|----------------|---------------------|-----------------------------------|----------------|----------------------|
| | | | | |

BASF Construction Chemicals Safety data sheet according to 91/155/EEC

Date / Revised: 2007/12/15

Version: 1.0

Product: **UCRETE HP HPQ NEUTRAL PTC**

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009

Component

| | | | |
|----------------------------|------|-------------------|-----|
| SILICA, CRYSTALLINE QUARTZ | LC50 | no data available | |
| PORTLAND CEMENT | LC50 | no data available | |
| IRON OXIDE | LC50 | 0.96 mg/l | 4 h |

Acute oral toxicity

| <u>Product</u> | <u>Type</u> | <u>Value</u> | <u>Species</u> |
|----------------|-------------|-------------------|----------------|
| | LD50 (Oral) | no data available | |

Component

| | | |
|----------------------------|-------------|-------------|
| SILICA, CRYSTALLINE QUARTZ | LD50 (Oral) | 1,300 mg/kg |
| PORTLAND CEMENT | LD50 (Oral) | 2,000 mg/kg |
| IRON OXIDE | LD50 (Oral) | 3,700 mg/kg |

Acute dermal toxicity

| <u>Product</u> | <u>Type</u> | <u>Value</u> | <u>Species</u> |
|----------------|---------------|-------------------|----------------|
| | LD50 (Dermal) | no data available | |

Component

| | | |
|----------------------------|---------------|-------------------|
| SILICA, CRYSTALLINE QUARTZ | LD50 (Dermal) | no data available |
| PORTLAND CEMENT | LD50 (Dermal) | no data available |
| IRON OXIDE | LD50 (Dermal) | 3,100 mg/kg |

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

| | | |
|------|------------------------|---------------|
| DOT | : Proper shipping name | Not regulated |
| IATA | : Proper shipping name | Not regulated |

15. REGULATORY INFORMATION**SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of

BASF Construction Chemicals Safety data sheet according to 91/155/EEC

Date / Revised: 2007/12/15

Version: 1.0

Product: **UCRETE HP HPQ NEUTRAL PTC**

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009

the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

DELAYED (CHRONIC) HEALTH HAZARD IMMEDIATE (ACUTE) HEALTH HAZARD

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

| <u>Weight %</u> | <u>CAS No.</u> | <u>Chemical Name</u> |
|-----------------|----------------|----------------------|
|-----------------|----------------|----------------------|

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

| <u>RQ</u> | <u>CAS No.</u> | <u>Chemical Name</u> |
|-----------|----------------|----------------------|
|-----------|----------------|----------------------|

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

| <u>CAS No.</u> | <u>Chemical Name</u> |
|----------------|----------------------|
|----------------|----------------------|

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

| <u>CAS No.</u> | <u>Chemical Name</u> |
|----------------|----------------------------|
| 14808-60-7 | SILICA, CRYSTALLINE QUARTZ |

16. OTHER INFORMATION

Legend : N.E. - Not Established
TLV - Threshold Limit Value
STEL - Short Term Exposure Limit
PEL - Permissible Exposure Limit
CEIL - Ceiling

Prepared By : Environment, Health and Safety Department

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

BASF Construction Chemicals Safety data sheet according to 91/155/EEC

Date / Revised: 2007/12/15

Version: 1.0

Product: **UCRETE HP HPQ NEUTRAL PTC**

(30416377/MDS_GEN_US/EN)

Date of print 15.10.2009
